



A photograph of a modern architectural space. On the left, a tall, textured concrete wall features several narrow, vertical rectangular openings that emit a warm, golden light. The floor is a smooth, light-colored concrete surface. In the foreground, a wide, flat concrete step or platform extends across the frame. The background shows a clear blue sky. The overall aesthetic is minimalist and contemporary.

STEP OUTDOOR

OUTDOOR

STEP OUTDOOR

Apparecchio da incasso a parete per illuminazione segnapasso direzionata con angolo di 20°, per sorgente LED integrata con alimentazione remota disponibile come accessorio. Corpo e cornice di battuta super-slim larghezza 5 mm. in metallo verniciato. Installabile anche in pareti e soffitti in calcestruzzo mediante apposita cassaforma in lamiera zincata disponibile come accessorio. Grado di protezione IP65.

Recessed downlight for wall installation, for guidance lighting with 20° angle direction, for integrated LED source with remote power-supply available as an accessory. Body and super-slim 5 mm width frame in painted metal. It can also be installed in concrete or brick walls through specific galvanized steel wall-box, available as an accessory. Degree of protection IP65.




UK CONFORMITY ASSESSMENT E EUROPEAN CERTIFICATION / UK CONFORMITY ASSESSMENT AND EUROPEAN CERTIFICATION



PRODOTTI COSTRUITI CON MATERIALE RICICLABILE / PRODUCTS MADE OF RECYCLABLE MATERIAL



GARANZIA DI 5 ANNI / 5-YEAR WARRANTY



IDONEI PER CARTONGESSO O LATERIZIO / CALCESTRUZZO CON APPOSITA CASSAFORMA OPZIONALE
SUITABLE FOR PLASTERBOARD OR BRICKWALL / CONCRETE WITH THE OPTIONAL BOX




IDONEI PER CAPPOTTI CON APPOSITA CASSAFORMA OPZIONALE / SUITABLE FOR COATS WITH THE OPTIONAL BOX

FINITURE STANDARD / STANDARD FINISHINGS

- | | | |
|-----|---|-----------------|
| /01 |  | BIANCO/WHITE |
| /02 |  | NERO/BLACK |
| /60 |  | CORTEN / CORTEN |

PHOTOMETRIC DATA



COMPOSIZIONE CODICE: xxx/##

HOW TO CREATE THE CODE:

CODE
F1000.8 /##
|
base code


/## FINITURA/FINISHING

- | | |
|---|---------------------|
|  | /01 bianco white |
|  | /02 nero black |
|  | /60 corten corten |

500

DRIVERS VEDI | SEE P.452


STEP 75



LED		Dim.		H	Kg	lm product/beam 3000K	CODE	500
W	mA	27x75	67	0,2	16°	252	LT1983BCIP/##	
1,5	500							

Accessori - accessories: LT1992: cassaforma step 75 - Wallbox step 75


STEP 150



LED		Dim.		H	Kg	lm product/beam 3000K	CODE	500
W	mA	27x70	142	0,4	16°	252	LT1982BCIP/##	
1,5	500							

Accessori - accessories: LT1991: cassaforma step 150 - Wallbox step 150

STEP 300




LED		Dim.		H	Kg	lm product/beam 3000K	CODE	500
W	mA	27x70	370	0,7	16°	252	LT1981BCIP/##	
1,5	500							

Accessori - accessories: LT1990: cassaforma step 300 - Wallbox step 300


ACCESSORI / ACCESSORIES

CASSAFORMA ADATTA ANCHE A I CAPPOTTI | WALLBOX SUITABLE FOR INSULATING COATS




	Dim.	H	CODE
STEP75	30x80	220	LT1992

Idonea anche per calcestruzzo. Suitable also for brickwall.



	Dim.	H	CODE
STEP150	30x80	265	LT1991

Idonea anche per calcestruzzo. Suitable also for brickwall.



	Dim.	H	CODE
STEP300	30x80	492	LT1990

Idonea anche per calcestruzzo. Suitable also for brickwall.