



STEP

STEP

Apparecchio da incasso a parete per illuminazione segnapasso direzionata con angolo di 20°, per sorgente LED integrata con alimentazione remota disponibile come accessorio. Corpo e cornice di battuta in metallo verniciato. Installabile anche in pareti e soffitti in calcestruzzo mediante apposita cassaforma in lamiera zincata disponibile come accessorio. Grado di protezione IP20.

Recessed wall luminaire for path lighting with 20 ° angle, for integrated LED source with remote power supply available as accessory. Body and frame in painted metal. It can, also, be installed in concrete or brick ceilings using a special galvanized metal outercasing available as accessory. IP20.



UK CONFORMITY ASSESSMENT E EUROPEAN CERTIFICATION / UK CONFORMITY ASSESSMENT AND EUROPEAN CERTIFICATION




PRODOTTI COSTRUITI CON MATERIALE RICICLABILE / PRODUCTS MADE OF RECYCLABLE MATERIAL



GARANZIA DI 5 ANNI / 5-YEAR WARRANTY



FISSO / FIXED



IDONEI PER CARTONGESSO O LATERIZIO / CALCESTRUZZO CON APPOSITA CASSAFORMA OPZIONALE
SUITABLE FOR PLASTERBOARD OR BRICKWALL / CONCRETE WITH THE OPTIONAL BOX


FINITURE STANDARD / STANDARD FINISHINGS

/01		BIANCO/WHITE
/02		NERO/BLACK
/60		CORTEN

FINITURE PREMIUM / PREMIUM FINISHINGS

/81		ORO ROSA/ROSE GOLD
/82		BRONZO ANTICATO/ ANTIQUE BRONZE
/83		OTTONE BRUNITO SPAZZOLATO/ BRUSHED BURNISHED BRASS

PHOTOMETRIC DATA



/ ## FINITURA | FINISHING

	/ 01 bianco white
	/ 02 nero black
	/ 60 corten corten

FASCIO / BEAM

16°

/ ## FINITURA PREMIUM / PREMIUM FINISHING

	/ 81 oro rosa / rose gold
	/ 82 bronzo anticato antique bronze
	/ 83 ottone brunito spazzolato brushed burnished brass

500 DRIVERS VEDI | SEE P.452

COMPOSIZIONE CODICE: xxx / ##
HOW TO CREATE THE CODE: **F1000 / 01**

CODE

F1000.8 / ## — finishing

base code



01




02



60

STEP 75




29X69 500 15 10 IP20 A 5 UK CE

LED	W	mA	Dim.	H	Kg	lm product/beam 3000K	CODE
1,5	500	27x75	67	0,2	252	16°	LT1983BC / ##

Accessori - accessories: LT1992: cassaforma step 75 - Wallbox step 75

STEP 150




29X144 500 15 10 IP20 A 5 UK CE

LED	W	mA	Dim.	H	Kg	lm product/beam 3000K	CODE
1,5	500	27x70	142	0,4	252	16°	LT1982BC / ##

Accessori - accessories: LT1991: cassaforma step 150 - Wallbox step 150

STEP 300




29X372 500 15 10 IP20 A 5 UK CE

LED	W	mA	Dim.	H	Kg	lm product/beam 3000K	CODE
1,5	500	27x70	370	0,7	252	16°	LT1981BC / ##

Accessori - accessories: LT1990: cassaforma step 300 - Wallbox step 300


ACCESSORI OPZIONALI / OPTIONAL ACCESSORIES

CASSAFORMA WALLBOX




	Dim.	H	CODE
STEP75	30x80	220	LT1992

Idonea anche per calcestruzzo. Suitable also for brickwall.



	Dim.	H	CODE
STEP150	30x80	265	LT1991

Idonea anche per calcestruzzo. Suitable also for brickwall.



	Dim.	H	CODE
STEP300	30x80	492	LT1990

Idonea anche per calcestruzzo. Suitable also for brickwall.