

I-SQUARE

RECESSED




FISSO | FIXED



INCLINABILE | ADJUSTABLE



FISSO | FIXED




NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED DISPONIBILI ANCHE VERSIONI 2700 / 4000K E FINITURA NERA / 02 | AVAILABLE VERSION 2700 / 4000K AND BLACK / 02 | FINISHING

taglio per incasso / recessed hole dimension  77X77




LED		Im product/beam		3000K		CODE	250	350
W	mA	LXW	H	F27°	W46°			
8	250	84.5X84.5	95	0,35	860	860	IS013.9	●● / ##
12	350	84.5X84.5	95	0,35	1285	1285		



LED		Im product/beam		3000K		CODE	350	500
W	mA	mm	H	F27°	W46°			
12	350	84.5X84.5	115	0,35	1285	1285	IS014.9	●● / ##
18	500	84.5X84.5	115	0,35	1575	1575		

GU10		Hmm		Kg	CODE	IS015
W	LXW	mm	H			
50	84.5X84.5	94	0.21			

INCLINABILE | ADJUSTABLE




NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED DISPONIBILI ANCHE VERSIONI 2700 / 4000K E FINITURA NERA / 02 | AVAILABLE VERSION 2700 / 4000K AND BLACK / 02 | FINISHING

taglio per incasso / recessed hole dimension  77X77



LED							Im product/beam 3000K		250	350
W	mA	mm	H	α	Kg	F27°	W46°	CODE		
8	250	84.5X84.5	95	30	0,35	860	860	IS016.9 ●● / ##		
12	350	84.5X84.5	95	30	0,35	1285	1285			



LED						Im product/beam 3000K		350	500
W	mA	mm	H	α	Kg	F27°	W46°	CODE	
12	350	84.5X84.5	115	30	0,35	1285	1285	ISO17.9 ●● / ##	
18	500	84.5X84.5	115	30	0,35	1575	1575		

GU10		Hmm		Kg	CODE	IS017
W	mm	H	mm			
50	84.5X84.5	94	0.21			

VERSIONI DISPONIBILI / AVAILABLE VERSION

● KELVIN

27 2700K
30 3000K
35 3500K
40 4000K

● FASCIO / BEAM



F Flood 27°
W Wide 46°

/ ## FINITURA | FINISHING

□ / 01 bianco | white
■ / 02 nero | black

COMPOSIZIONE CODICE: xxx.x ●● /

HOW TO CREATE THE CODE: F1000.8 27S / 01

CODE
F1000.8 | ●● | ## | — finishing
base code kelvin beam

250 350 500 DRIVERS VEDI | SEE P.452 59